GILSULATE INTERNATIONAL, INC. MATERIAL SAFETY DATA SHEET

I. Product Identification						
Trade Name (as labeled):	Gilsula	te 500XR				
Manufacturer's Name: Address: Phone Number:	26000	te International, Inc Springbrook Ave #2 99-3881		CA 91350 • P.O. B	ox 802650	
Date Prepared or Revised:	March	1, 2012				
		II. Prod	luct Ingredients			
Chemical Names		CAS Numbers		xposure Limits in A		
Sodium Potassium Aluminum S Calcium Carbonate	Silicate	93763-70-3 1317-65-3	ACGIH TL\ 10 mg/M ³ 10 mg/M ³	15 mg/N	1 ³	
Calcium Carbonate may contain amounts of crystalline silica as		1317-05-3	TO HIG/M	15 119/1	1	
impurity (less than 0.3%)		14808-60-7	0.1 mg/M ³	0.1 mg/N	Л ³	
III. Physical Properties						
Vapor Density (air=1)		N/A	Melting point or		2000+	
Specific Gravity (Water=1)		N/A	Boiling point or		N/A	
Solubility in Water:		Hydrophobic Evaporation rate (butyl acetate=1) N/A) N/A		
Vapor Pressure, mmHg at 20°C:N/A Appearance and odor: White to off white powder, no odor.						
HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist): Visual only, may be dusty. No gas, vapors, or mist emitted.						
IV. Fire and Explosion						
Flash Point, °F (Give method):		Non-flammable.	· ·			
Auto ignition temperature, °F:	N/A					
Flammable limits in air, Volume	%:	N/A	Lower (LEL):	N/A L	Jpper (UEL): N/A	
Special fire fighting procedures	: N/A		Unusual fire an	d explosion hazard	is: N/A	
V. Health Hazard Information						
A) Symptoms of overexposure for each potential route of exposure Inhaled: Coughing						
Contact with skin or eyes: Possible eye irritation from dust particles; wear eye protection						
Absorbed through skin:	N/A		. ,			
Swallowed:	N/A					

B) Health effects or risks from exposure

Acute: None.

Chronic: Excessive inhalation over long period may cause harmful irritation, use NIOSH approved mask for nuisance dust. The calcium carbonate component in this product may contain trace amounts of crystalline silica (quartz) as an impurity. Chronic exposure to crystalline silica dust at concentrations exceeding occupational exposure limits may cause silicosis. IARC has classified crystalline silica as a probable human carcinogen.

As of the date of preparation of this document, the information contained herein is believed to be accurate and is provided in good faith to comply with applicable federal, state, and local laws. However, no warranty or representation with respect to such information is intended or given. Gilsulate International, Inc. is a women-owned small business headquarted in the state of California.

C) First Aid: Emergency procedures Eye contact: Attempt to wash out with clear water; if unable have particle removed by doctor. Skin contact: None Inhaled: Remove affected individual from dusty area to area with clean air Swallowed: None						
D) Suspected Cancer Agent? <u>X</u> NO: This products ingredients are not found in the lists below:						
YES: Federal OSHA	NTPIARC					
E) Medical conditions aggravated by exposure Any respiratory illness which may be aggravated by a nuisance dust.						
VI. Reactivity Data						
Stability: X_Stable Unstable Incompatibility (Materials to avoid): Hydrofluoric Acid, Flourine Unstable Hazardous decomposition products (including combustion products): None Hazardous Polymerization: May Occur X_Will not occur Conditions to avoid: None						
VII. Spill, Leak, and Disposal Procedures						
Spill response procedures (include employee protection measures): Vacuum clean or sweep material; Use respirators suitable for nuisance dust and eye protection						
Preparing wastes for disposal (container types, neutralization, etc.): Dispose in bulk or containers according to local dump requirements. No special treatment required.						
Note: Dispose of all wastes in accordance with federal, state, and local regulations.						
VIII. Special Handling Information						
Ventilation and engineering controls:	Respirator protection (type)					
Maintain dust level below TLV. Eye Protection (type)	NIOSH approved masks suitable for nuisance dust. Gloves (specify material)					
Protective goggles	Not required					
Other clothing and equipment Not required	Work practices, hygienic practices Use good housekeeping to avoid transient dust					
Other handling and storage requirements Use good housekeeping to avoid transient dust	National Motor Freight Classification: Class 50					
Protective measures during maintenance of contaminated equipment None special other than NIOSH approved masks and goggles						